#### Large Med 1200 - Pharmacy Refrigerator

# **Glass Door: DLS1400PG**

### Overview

Our intuitive range of refrigerators feature built-in wireless monitoring software, enabling you to access the refrigerator's performance remotely.

Plus, our bespoke touchscreen controller, designed specifically for the end user with simple access to key information.



## **Key Features**



Advanced Controller Easy to use touch screen controller, with no awkward buttons to press



Connected Wireless temperature monitoring built-in



Dual Temperature Probes View your daily minimum and maximum temperatures in one touch



Battery Back-Up A/V alarms should your temperature stray or the door be left open



Antimicrobial Protection Biocote® handle helping protect from microbes such as E. coli, Campylobacter, Salmonella and MRSA



Self-Closing Doors Fitted with self-closing hinges to help avoid any temperature loss

#### **DLS1400PG - Product Specification**

Counter Top	
Model	DLS1400PG
Gross Capacity (Litres)	1400
Net Capacity (Litres)	964
Unit External Width (mm)	1440
Unit External Depth (mm)	800 (excl handle)
Unit External Height (mm)	2040
Packed Width (mm)	1520
Packed Depth (mm)	910
Packed Height (mm)	2260
Packed Weight (kg)	290
Internal Dimensions (mm) (WxDxH)	1320x665x1530
Temperature Range	+2C to +8C
External Finish	Pre-coated steel
Internal Finish	Stainless Steel
Type of Plastic	
Door Type	1 x Right hand / 1 X Left Hand hinged
Door Style	Glass / Self Closing
Open Door Depth	1465mm
Replaceable Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes / Mechanical
Adjustable Feet	Castors x4
Porthole	Yes
Porthole Size	32mm
Temperature Display On Panel	LED / Touchscreen
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number Of Shelves	10
Number Of Shelf Positions	20
Shelf Size	530x650mm
Shelf Material	PVC coated wire
Number Of Baskets	0
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	Yes
Spark Free	No
Defrost Setting	Auto
Controller Type	Digital / Wireless
Battery Back Up	Yes
Controller Connectivity	Wireless / SD Download
Number Of Probes	2
Probe Type	Air / Load
Ambient Temperature Range	10 - 32C
Refrigerant Type	R290
Plug Type	UK
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Insulation Thickness	58mm
Anti Microbial Handle	Yes / BioCote







