

Counter Top - Pharmacy Refrigerator

Glass Door: DLS145PG

Overview

Our intuitive range of refrigerators feature built-in wireless monitoring software, enabling you to access the refrigerator's performance remotely.

Plus, our bespoke touchscreen controller, designed specifically for the end user with simple access to key information.



Key Features



Advanced Controller

Easy to use touch screen controller, with no awkward buttons to press



Connected

Wireless temperature monitoring built-in



Dual Temperature Probes

View your daily minimum and maximum temperatures in one touch



Battery Back-Up

A/V alarms should your temperature stray or the door be left open



Antimicrobial Protection

Biocote® handle helping protect from microbes such as E. coli, Campylobacter, Salmonella and MRSA



Self-Closing Doors

Fitted with self-closing hinges to help avoid any temperature loss

DLS145PG - Product Specification

Counter Top	
Model	DLS145PG
Gross Capacity (Litres)	145
Net Capacity (Litres)	136
Unit External Width (mm)	595
Unit External Depth (mm)	660 (excl handle)
Unit External Height (mm)	855
Packed Width (mm)	605
Packed Depth (mm)	660
Packed Height (mm)	860
Packed Weight (kg)	34
Internal Dimensions (mm) (WxDxH)	500x400x680
Temperature Range	+2C to +8C
External Finish	Pre-coated steel
Internal Finish	Plastic & Aluminium
Type of Plastic	HIPS (Food grade)
Door Type	Right hand Hinged
Door Style	Glass / Self Closing
Open Door Depth	1215
Replaceable Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes / Mechanical
Adjustable Feet	One
Porthole	Yes
Porthole Size	16mm
Temperature Display On Panel	LED / Touchscreen
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number Of Shelves	3
Number Of Shelf Positions	6
Shelf Size	515 x 424
Shelf Material	PVC coated wire
Number Of Baskets	1
Basket Size	494x265x148
Basket Material	PVC coated wire
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	Yes
Spark Free	No
Defrost Setting	Auto
Controller Type	Digital / Wireless
Battery Back Up	Yes
Controller Connectivity	Wireless / SD Download
Number Of Probes	2
Probe Type	Air / Load
Ambient Temperature Range	10 - 32C
Refrigerant Type	R600a
Plug Type	UK
Voltage Supply	220-240V
Frequency (Hz)	50Hz
Insulation Thickness	37
Anti Microbial Handle	Yes / BioCote