

Series 4 1200

LMS by Dulas Life Sciences

Reliable and accurate temperature control.

Our cooled incubators offer optimum temperature control from -10°C to $+50^{\circ}\text{C}$ with an average variation of 0.5°C and fluctuation of 0.1°C , or 0°C to $+60^{\circ}\text{C}$ upon request.

LMS has been producing scientific incubation products since 1979.



Key Features



Door lock

Preventing unauthorised access



Defrost

Automatic, with a manual override option built in



Fruit fly modification

Prevents corrosion caused by fruit flies



Self-evaporating drip tray

For additional temperature probes



Fan assisted air circulation

Keeping temperatures consistent



Heating / Cooling control

Optimising power usage when needed

Cooled Incubator - Stainless Steel Interior

| Series 4 | | |
|-----------------|--|-----------------|
| Standard | Model | 1200 |
| | RJ45 interface for remote access (wired) | Yes |
| | Capacity (L) | 1200 |
| | Material | Stainless steel |
| | Chamber material | Stainless steel |
| | Temperature range | -10°C to +50°C |
| | Accuracy | +0.5°C |
| | Height exterior (mm) | 2080 |
| | Width exterior (mm) | 1500 |
| | Depth exterior (mm) | 900 |
| | Shelf size (mm) | 530 x 550 |
| | Weight (kg) | 235 |
| | Number of shelves | 10 |
| | Fruit fly modification | Yes |
| | Access porthole | Yes |
| Optional extras | Programmable controller | Yes |
| | Dual temperature control | Yes |
| | Double glazed door* | Yes |
| | Inner perspex door | Yes |
| | Extra shelves | Yes |
| | Fully programmable interior illumination | Yes |
| | Independent 24 hour / 7 day timer | Yes |
| | High / low AV alarm | Yes |
| | Integral chart recorder | Yes |
| | Internal 13A socket (EU/UK) | Yes |
| | Drying mode | Yes |
| | Corrosive conditions evaporator | Yes |
| | Pre-programming service | Yes |